

Overview

EXO® is a modularized platform that supports a wide variety of connectivity types and applications on the same 1RU chassis, allowing for flexibility now and growth in the future.

EXO® supports up to four cassette and feed-through modules. Modules can be mixed to match your connectivity requirements. There are modules for fiber, copper, wavelength, and optical power management, supporting 1G, 10G, 40G, and 100/120G connectivity. With 48 diverse ports, the EXO® platform offers flexibility and space savings.


EXO® modules allows scalability as data center connectivity needs change. With the ability to plug in exactly the modules needed now and in the future, EXO® is a grow on demand platform.

Features and Benefits

- 1 RU Modular Fiber, Copper, Wavelength & Power Management Panel
- Swappable Modules
- 10/40/100G Plug-n-Play
- Connectivity Options Include: RJ45, SFP+, QSFP+, LC, MXC, MTP®
- 8F, 12F, 24F MTP® Options
- Built-In Wire Manager
- Removable Doors with Labels
- Fully Passive, No Added Heat or Cooling Load

A Smaller Footprint - EXO® mini


EXO® mini introduces the industry's newest form factor – smaller, modular and smarter. Facilitating a wire to wire connection to the maximum network performance, EXO mini offers RJ45, LC and MTP® feed-through connections. Functionality comes with elegance.



Features and Benefits

- Compact and Efficient, 1U, Zero Power Consumption
- Flexible Modular Solutions, Mix Between SFP+ DAC, MXC, Duplex LC, CAT5e/CAT6 RJ45 and MTP® Feed-Through
- Add Up to 48 Ports of SFP+ DAC, Duplex LC, CAT5e/CAT6 and MTP® Adapters

Cassettes and Feed-Throughs




MXC[®] Feed-Through



LC-LC Feed-Through



MTP[®] Feed-Through



LC Casette



SFP+ Casette

RJ45 Feed-Through

EXO[™] Connectivity Hub Specifications

Item	Description
Cassettes	12, SFP+ through ports on each cassette for a total of up to 48 ports
Height	1 RU (1.75 in., 43.5 mm)
Width	482 mm
Depth	96 mm
Weight	3 kg; 3.3 kg gross (when loaded with 4 cassettes)
Temperature	-40°C to 75°C Storage 0°C to 40°C Operating
Access	Front and rear
Power	No power required

Standards Compliance

- SFF-8431 compliant
- RoHS



Product Selection

Product	Part Number
EXO 1U Chassis	88EXO-1U00-4
EXO Mini	88EXOM-1U00-4
EXO Module: 12x CAT6 RJ45 Feed-Through	88EXO71-0000-12
EXO Module: 12 Duplex LC-LC Feed-Through	88EXO31-0000-AQ12
EXO Adapter: 6x MTP Feed-Through (100/120GbE Pass-Through)	88EXO50-0000-BK6
EXO Adapter: 6x MTP Feed-Through (40GbE Pass-Through)	88EXO50-0000-GY6
EXO Cassette: 1x12 MTP to 12 LC Duplex MM OM4 (100/120GbE to 10GbE Breakout)	88EXO51-8020-1x12
EXO Cassette: 2x12 MTP to 12 LC Duplex MM OM4 (40GbE to 10GbE Breakout)	88EXO51-8020-2x12